

MODEL	NUMBER of ROWS	ROW SPACING	NUMBER of TIRES	FOLD // FLEX	OPEN WIDTH ^(A) // FOLDED WIDTH ^(B)	OPEN LENGTH ^(C) // FOLDED LENGTH ^(D)	HITCH TYPE	TIRE POSITION	PAGE #
PB2015FR	15	15"	1-2-1	4-7-4 // 4-7-4	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]	14
PB2020FR	12	20"	1-2-1	3-6-3 // 3-6-3	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]	15
PB2030FR	8	30"	1-2-1	2-4-2 // 2-4-2	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]	16
PB2030BR	8	30"	1-2-1	2-4-2 // 2-4-2	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	BACK RUNNING [‡]	17
PB3015FR⁽¹⁾	23*	15"	1-4-1	6-11-6 // 6-11-6	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]	20
PB3020FR⁽¹⁾	18	20"	1-4-1	5-8-5 // 5-8-5	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]	21
PB3022FR⁽¹⁾	16	22"	1-4-1	4-8-4 // 4-8-4	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]	22
PB3030FR⁽¹⁾	12	30"	1-4-1	3-6-3 // 3-6-3	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]	23
PB3030BR	12	30"	1-4-1	4-4-4 // 3-6-3	30' 10" // 128"	15' 2" // 23' 10"	HAMMER*	BACK RUNNING [‡]	24
PB3030BRT	12	30"	1-4-1	4-4-4 // 3-6-3	30' 10" // 128"	15' 2" // 23' 10"	2PT (CAT3)	BACK RUNNING [‡]	25
PB4015FR⁽¹⁾	31*	15"	2-4-2	10-11-10 // 10-11-10	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]	28
PB4020FR⁽¹⁾	24	20"	2-4-2	8-8-8 // 8-8-8	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]	29
PB4030FR	16	30"	2-4-2	5-6-5 // 5-6-5	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]	30
PB4030BR	16	30"	2-4-2	6-4-6 // 5-6-5	41' // 128"	18' 11" // 27' 6"	HAMMER*	BACK RUNNING [‡]	31
PB4030BRT	16	30"	2-4-2	6-4-6 // 5-6-5	41' // 128"	18' 11" // 27' 6"	2PT (CAT3)	BACK RUNNING [‡]	32
PB4422FR	24	22"	2-4-2	8-8-8 // 8-8-8	43' 6" // 164 ¼"	19' 11" // 29' 6"	HAMMER*	FRONT RUNNING [†]	33
PB6015FR^(3,4)	47*	15"	2-4-2	18-11-18 // 18-11-18	59' 10" // 164 ¼"	24' 7" // 39' 6"	HAMMER*	FRONT RUNNING [†]	36
PB6020FR⁽⁴⁾	36	20"	2-4-2	14-8-14 // 14-8-14	59' 10" // 164 ¼"	24' 7" // 39' 6"	HAMMER*	FRONT RUNNING [†]	37
PB6030FR	24	30"	2-4-2	9-6-9 // 9-6-9	59' 10" // 164 ¼"	24' 7" // 39' 6"	HAMMER*	FRONT RUNNING [†]	38
PB6030BR	24	30"	2-4-2	10-4-10 // 9-6-9	59' 10" // 128"	24' 7" // 39' 6"	HAMMER*	BACK RUNNING [‡]	39
PB6030BRT	24	30"	2-4-2	10-4-10 // 9-6-9	59' 10" // 128"	24' 7" // 39' 6"	2PT (CAT 3)	BACK RUNNING [‡]	40
PB6622FR⁽⁴⁾	36	22"	2-4-2	14-8-14 // 14-8-14	65' 6" // 164 ¼"	NA	HAMMER*	FRONT RUNNING [†]	41

(MODEL)¹ Right hand wing tire located on outside of right wing outer row unit
 (MODEL)³ CSD model only
 (MODEL)⁴ Requires 3 vac fans
 (# of Rows)* Even row spacings are available. (24, 32, 48)
 HAMMER* BULL PULL™ brand hammer strap hitch
 FRONT RUNNING[†] Tire: 20' & 30': Bartread // 40' & up: 420 55R 22.5 on center, Bartread on wings.
 BACK RUNNING[‡] Tire: 30' & up: 255 70R 22.5

Manufacturer reserves the right to make changes at any time, without notice, to prices, specifications, & models.

